

SWANA

PERFECTION OF A STAR

INTERNATIONAL RING SIZE CONVERSION CHART

use this chart to convert your local standard to the US ring sizes for ordering.

U.S.Size	Diameter in inches	Diameter in MM	Metric MM Equivalent	British	French	German	Japanese	Swiss
0000	.390	9.91		-				
00	.422	10.72		-				
0	.454	11.53		-				
1/2	.474	11.95		A				
3/4	.482	12.18		A 1/2				
1	.487	12.37	38.9	B			1	
1 1/4	-	12.60	39.6	B 1/2				
1 1/2	.503	12.78	40.2	C				
1 3/4	-	13.00	40.8	C 1/2				
2	.520	13.21	41.5	D	41 1/2	13 1/2	2	1 1/2
2 1/4	-	13.41	42.1	D 1/2				
2 1/2	.536	13.61	42.7	E	42 3/4	13 3/4	3	2 3/4
2 3/4	-	13.83	43.4	E 1/2	-	-		
3	.553	14.05	44.0	F	44	14	4	4
3 1/8	-	14.15	44.3	F 1/2	-	-		
3 1/4	-	14.25	44.6	-	-	-		
3 3/8	-	14.36	44.9	G	45 1/4	-	5	5 1/4
3 1/2	.569	14.45	45.2	-	-	14 1/2		
3 5/8	-	14.56	45.6	G 1/2	-		6	
3 3/4	-	14.65	45.9	H	46 1/2			6 1/2
4	.585	14.86	46.5	H 1/2	-	15	7	

U.S.Size	Diameter in inches	Diameter in MM	Metric MM Equivalent	British	French	German	Japanese	Swiss
4 1/4	-	15.04	47.1	I	47 3/4			7 3/4
4 1/2	.601	15.27	47.8	I 1/2	-	15 1/4	8	
4 5/8	-	15.40	48.1	J	49	15 1/2		9
4 3/4	-	15.53	48.4	-	-			
5	.618	15.70	49.0	J 1/2	-	15 3/4	9	
5 1/8	-	15.80	49.3	K	50			10
5 1/4	-	15.90	49.6	-	-			
5 3/8	-	16.0	50.0	K 1/2	-		10	
5 1/2	.634	16.10	50.3	L	51 3/4	16		11 3/4
5 3/4	-	16.30	50.9	-	-			
5 7/8	-	16.41	51.3	L 1/2	55 1/4			
6	.650	16.51	51.5	M	-	16 1/2	12	12 3/4
6 1/4	-	16.71	52.2	M 1/2	56 3/4			
6 1/2	.666	16.92	52.8	N	-	17	13	14
6 3/4	-	17.13	53.4	N 1/2	57 3/4			
7	.683	17.35	54.0	O	-	17 1/4	14	15 1/4
7 1/4	-	17.45	54.7	O 1/2	-			
7 1/2	.699	17.75	55.3	P	59	17 3/4	15	16 1/2
7 3/4	-	17.97	55.9	P 1/2	-			
8	-	18.19	56.6	Q	-	18	16	17 3/4
8 1/4	.732	18.35	57.2	Q 1/2	-			
8 1/2	-	18.53	57.8	-	60 1/4	18 1/2	17	
8 5/8	-	18.61	58.4	R	-			19
8 3/4	-	18.69	58.4	-	-			
8 7/8	.748	18.80	59.0	R 1/2	-			

U.S.Size	Diameter in inches	Diameter in MM	Metric MM Equivalent	British	French	German	Japanese	Swiss
9	-	18.89	59.1	-	-		18	
9 1/8	-	19.10	59.4	S	60 1/4			20 1/4
9 1/4	-	19.22	59.7	-	-			
9 3/8	-	19.31	60.0	S 1/2	-			
9 1/2	.764	19.41	60.3	-	-	19 1/2	19	
9 5/8	-	19.51	60.6	T	61 1/2			21 1/2
9 3/4	-	19.62	60.9	-	-			
10	.781	19.84	61.6	T 1/2	-	20	20	
10 1/4	-	20.02	62.2	U	62 3/4		21	22 3/4
10 1/2	.797	20.02	62.8	U 1/2	-	20 1/4	22	
10 5/8	-	20.32	63.1	V	63			23 3/4
10 3/4	-	20.44	63.5	-	-			
11	.814	20.68	64.1	V 1/2	-	20 3/4	23	
11 1/8	-	20.76	64.3	W	65			25
11 1/4	-	20.85	64.7	-	-			
11 3/8	-	20.94	65.0	W 1/2	-			
11 1/2	-	21.08	65.3	-	-	21	24	
11 5/8	.830	21.18	65.7	X	66 1/4			26 1/4
11 3/4	-	21.24	66.0	-	-			
11 7/8	-	21.30	66.3	X 1/2	-			
12	.846	21.49	66.6	Y	67 1/2	21 1/4	25	27 1/2
12 1/4	-	21.69	67.2	Y 1/2	-			
12 1/2	.862	21.89	67.9	Z	68 3/4	21 3/4	26	28 3/4
12 3/4	-	22.10	68.5	Z 1/2	-			
13	.879	22.33	69.1	-	-	22	27	